# ift-Nachweis



## **Classification Report**

Number 21-001708-PR03 (NW-A01-0203-en-01)

Owner Europa Profil Aluminio S.A.

56th Klm National Highway

Athens - Lamia 32011 Innofita Viotas

Greece

Product Single sash lift-sliding door

Designation System: EUROPA ESS47

Shipping name: ESS 47 - Single sash lift & sliding door

Details Manufacturer Europa Profil Aluminio S.A., - Innofita Viotas;

Material Aluminium system with thermal break; Type of opening Lifting sliding; Opening direction To the right (seen from inside);

Overall dimensions (W x H) 1600 mm x 2200 mm

Special features Test sequence. The vapour pressure equalisation of the glazing

rebate has to be ensured. Material compatibility must be taken into account. Material durability must be taken into account. The strength, durability and material compatibility of the adhesive

system was not part of the test and is tested separately.

Result

Operating forces according to EN 13115:2001-07

A Rosenbully

Class: 1

Air permeability according to EN 12207:2016-12



Class: 3

Resistance to wind load according to EN 12210:2016-03




Class: C3/B3

Watertightness according to EN 12208:1999-11



Class: 9A

ift Rosenheim 14.04.2021



Dimitrios Moustakidis, MSc, Dipl.-Ing. Operating Testing Officer Building Component Testing



EN 14351-1:2006+A2:2016-09
\*) and corresponding national versions
(e.g. DIN EN)

Test report: 21-001708-PR03 PB-A01-0203-en-01

Representation



#### Instructions for use

The Evidence ("Nachweis") can be used for preparing the Declaration of Performance in accordance with the Construction Products Regulation 305/2011/EU. The results obtained apply to the direct field of application determined in Annex E of EN 14351-1.

### Validity

There is no time limit.

When using this document the upto-dateness of above basis and the conformity of the product have to be observed.

#### Notes on publication

The ift-Guidance Sheet "Conditions and Guidance for the Use of ift Test Documents" applies.

Identity-Check



www.ift-rosenheim.de/ift-geprueft ID: D30-EF2DC



